




Heavy Duty



3M™ Heavy Duty Duct Tape DT11

**Adhesive Type:**

Synthetic/Natural Rubber Blend

Maximum Operating Temperature:

150°F (66°C)

Tensile Strength:

29 lb/in (50.8 N/cm)

Adhesion to Steel: 88 oz/in (9.6 N/cm)**Elongation:** 19%**Thickness:** 0.27 mm (11 mil)

Applications: Securing temporary flooring, pipe sealing, hanging heavy poly drapes and reinforcing.

3M
Choice

Balanced
Construction

3M™ Super Duty Duct Tape DT17

**Adhesive Type:**

Synthetic/Natural Rubber Blend

Maximum Operating Temperature:

150°F (66°C)

Tensile Strength:

38 lb/in (66.5 N/cm)

Adhesion to Steel: 85 oz/in (9.3 N/cm)**Elongation:** 18%**Thickness:** 0.43 mm (17 mil)

Applications: Excellent for repairing, seaming, extra-strength bundling and protecting metal parts and surfaces from sandblast over-spray.

High
Abrasion
Resistance

3M™ Heavy Duty Duct Tape 3939

**Adhesive Type:** Rubber**Maximum Operating Temperature:**

200°F (93°C)

Tensile Strength:

27 lb/in (47.3 N/cm)

Adhesion to Steel: 58 oz/in (6.3 N/cm)**Elongation:** 17%**Thickness:** 0.22 mm (8.6 mil)

Applications: Ideal for use in maintenance, repair and construction applications.

Removes cleanly for up to one month from many opaque, non-glass surfaces when applied indoors.

3M™ Extra Heavy Duty Duct Tape 6969

**Adhesive Type:** Rubber**Maximum Operating Temperature:**

200°F (93°C)

Tensile Strength:

34 lb/in (59.5 N/cm)

Adhesion to Steel: 51 oz/in (5.6 N/cm)**Elongation:** 16%**Thickness:** 0.25 mm (10 mil)

Applications: Heavy duty solution for maintenance, repair and construction.

Fine Line Masking Tape

Product	Adhesive Type	Thickness	Max Operating Temperature	Tensile Strength	Adhesion to Steel	Elongation	Clean Removability
218	Rubber	5 mil (0.13 mm)	250°F (121°C)	13 lb/in (22.8 N/cm)	37 oz/in (4 N/cm)	720%	N/A
4737TL	Rubber	5.1 mil (0.13 mm)	300°F (149°C)	256 lb/in (28 N/cm)	26 oz/in (2.8 N/cm)	75%	N/A
215	Rubber	4.8 mil (0.12 mm)	250°F (121°C)	15 lb/in (26.3 N/cm)	43 oz/in (4.7 N/cm)	1150%	N/A
4737T	Rubber	5.1 mil (0.13 mm)	300°F (149°C)	16 lb/in (28 N/cm)	15 oz/in (1.6 N/cm)	75%	N/A
265	Silicone-Rubber	5.1 mil (0.13 mm)	200°F (93°C)	21 lb/in (36.8 N/cm)	21 oz/in (2.3 N/cm)	881%	N/A
2800	Acrylic	4.1 mil (0.105 mm)	300°F (149°C)	25 lb/in (43 N/cm)	16 oz/in (1.75 N/cm)	1000%	N/A
4735L	Rubber	5.4 mil (0.137 mm)	300°F (149°C)	14 lb/in (24.5 N/cm)	16 oz/in (1.7 N/cm)	130%	N/A
4737SL	Rubber	5.1 mil (0.13 mm)	300°F (149°C)	14 lb/in (24.5 N/100mm)	15 oz/in (1.6 N/cm)	75%	N/A
4735	Rubber	5.4 mil (0.137 mm)	300°F (149°C)	14 lb/in (24.5 N/cm)	9.5 oz/in (1 N/cm)	130%	N/A

Duct Tape

Utility

Product	Adhesive Type	Thickness	Max Operating Temperature	Tensile Strength	Adhesion to Steel	Elongation	Clean Removability
DT8	Synthetic/ Natural Rubber Blend	8 mil (0.2 mm)	150°F (65.5°C)	24 lb/in (42 N/cm)	74 oz/in (8.1 N/cm)	19%	N/A
1900	Synthetic Rubber	5.8 mil (0.147 mm)	200°F (93°C)	19 lb/in (33 N/cm)	62 oz/in (6.8 N/cm)	15%	N/A
3900	Rubber	7.6 mil (0.19 mm)	200°F (93°C)	28 lb/in (49 N/cm)	53 oz/in (5.8 N/cm)	19%	N/A
3903	Rubber	7.3 mil (0.19 mm)	200°F (93°C)	14.5 lb/in (25.3 N/cm)	15.4 oz/in (1.7 N/cm)	134%	N/A

Heavy Duty

Product	Adhesive Type	Thickness	Max Operating Temperature	Tensile Strength	Adhesion to Steel	Elongation	Clean Removability
DT11	Synthetic/ Natural Rubber Blend	11 mil (0.27 mm)	150°F (65.5°C)	29 lb/in (50.8 N/cm)	88 oz/in (9.6 N/cm)	19%	N/A
DT17	Synthetic/ Natural Rubber Blend	17 mil (0.43 mm)	150°F (65.5°C)	38 lb/in (66.5 N/cm)	85 oz/in (9.3 N/cm)	18%	N/A
3939	Rubber	8.6 mil (0.22 mm)	200°F (93°C)	27 lb/in (47.3 N/cm)	58 oz/in (6.3 N/cm)	17%	N/A
6969	Rubber	10 mil (0.25 mm)	200°F (93°C)	34 lb/in (59.5 N/cm)	51 oz/in (5.6 N/cm)	16%	N/A

Clean Removal

Product	Adhesive Type	Thickness	Max Operating Temperature	Tensile Strength	Adhesion to Steel	Elongation	Clean Removability
8979	Rubber	11.5 mil (0.29 mm)	200°F (93°C)	36.5 lb/in (64 N/cm)	57 oz/in (6.2 N/cm)	17%	6 month Clean Removal
8979N	Rubber	11.7 mil (0.3 mm)	200°F (93°C)	36 lb/in (63 N/cm)	48 oz/in (5.3 N/cm)	19%	6 month Clean Removal
5959	Natural/ Synthetic Rubber Blend	11 mil (0.28 mm)	200°F (93°C)	36 lb/in (63 N/cm)	57 oz/in (6.2 N/cm)	16%	3 month weather resistance
5903	Synthetic Rubber	7.5 mil (0.19 mm)	173°F (78°C)	21 lb/in (36.8 N/cm)	79 oz/in (8.7 N/cm)	72%	1 month weather resistance

Gaffers Tape

Product	Adhesive Type	Thickness	Max Operating Temperature	Tensile Strength	Adhesion to Steel	Elongation	Clean Removability
GT1	Synthetic Rubber	11 mil (0.27 mm)	200°F (93°C)	896 oz/in (98.1 N/100 mm)	72 oz/in (7.9 N/cm)	6%	N/A

Duct Tape (Cont.)

UPC	3M ID	Product	Stocked or MTO
Heavy Duty (Cont.)			
00051131069756	7000028933	3M™ Heavy Duty Duct Tape 3939, Silver, 48 mm x 54.8 m, 9.0 mil, 24 per case, Individually Wrapped Conveniently Packaged	Stocked
00021200855634	7100022015	3M™ Heavy Duty Duct Tape 3939, Silver, 96 mm x 54.8 m, 9.0 mil, 12 per case	Stocked
00021200855627	7000048815	3M™ Heavy Duty Duct Tape 3939, Silver, 72 mm x 54.8 m, 9.0 mil, 12 per case	Stocked
00021200227738	7000001232	3M™ Extra Heavy Duty Duct Tape 6969, Black, 48 mm x 54.8 m, 10.7 mil, 24 per case, Individually Wrapped Conveniently Packaged	Stocked
00021200227806	7000123814	3M™ Extra Heavy Duty Duct Tape 6969, Olive, 48 mm x 54.8 m, 10.7 mil, 24 per case, Individually Wrapped Conveniently Packaged	Stocked
00051131069695	7000001230	3M™ Extra Heavy Duty Duct Tape 6969, Silver, 48 mm x 54.8 m, 10.7 mil, 24 per case, Individually Wrapped Conveniently Packaged	Stocked
00021200856358	7000001231	3M™ Extra Heavy Duty Duct Tape 6969, Silver, 72 mm x 54.8 m, 10.7 mil, 12 per case	Stocked
Clean Removal			
00051131178199	7100140217	3M™ Performance Plus Duct Tape 8979, Olive, 48 mm x 55 m, 12.1 mil, 24 per case	Stocked
00048011539188	7000124266	3M™ Performance Plus Duct Tape 8979, Black, 48 mm x 54.8 m, 12.1 mil, 24 per case, Conveniently Packaged	Stocked
00051115259128	7100139310	3M™ Performance Plus Duct Tape 8979, Black, 72 mm x 54.8 m, 12.1 mil, 12 per case	Stocked
0005111916438	7100139301	3M™ Performance Plus Duct Tape 8979, Black, 12 in x 60 yd, 12.1 mil, 1 per case	Make to Order
0005111922125	7100005781	3M™ Performance Plus Duct Tape 8979, Black, 29 in x 60 yd, 12.1 mil, 1 per case	Make to Order
00051131178199	7100140217	3M™ Performance Plus Duct Tape 8979, Olive, 48 mm x 55 m, 12.1 mil, 24 per case	Stocked
00076308145293	7100160397	3M™ Performance Plus Duct Tape 8979, Olive, 27-1/2 in x 60 yd, 1 per case	Make to Order
0005111923290	7000049575	3M™ Performance Plus Duct Tape 8979, Olive, 29 in x 60 yd, 12.1 mil, 1 per case	Make to Order
00048011539225	7000124257	3M™ Performance Plus Duct Tape 8979, Slate Blue, 24 mm x 54.8 m 12.1 mil, 48 per case	Stocked
00048011538518	7000001329	3M™ Performance Plus Duct Tape 8979 Slate Blue, 48 mm x 22.8 m 12.1 mil, 12 per case, Conveniently Packaged	Stocked
00021200564680	7000001330	3M™ Performance Plus Duct Tape 8979, Slate Blue, 48 mm x 54.8 m, 12.1 mil, 24 per case, Conveniently Packaged	Stocked
00021200564697	7000124263	3M™ Performance Plus Duct Tape 8979, Slate Blue, 72 mm x 54.8 m, 12.1 mil, 12 per case	Stocked
00021200564703	7000049207	3M™ Performance Plus Duct Tape 8979, Slate Blue, 96 mm x 54.8 m, 12.1 mil, 12 per case	Stocked
00051138949280	7100139308	3M™ Performance Plus Duct Tape 8979, Slate Blue, 7 in x 60 yd, 12.1 mil, 6 per case	Make to Order
00048011539201	7000124267	3M™ Performance Plus Duct Tape 8979, Slate Blue, 12 in x 60 yd, 12.1 mil, 2 per case	Stocked
00048011581835	7000124264	3M™ Performance Plus Duct Tape 8979, Slate Blue, 144 mm x 54.8 m, 12.1 mil, 6 per case	Stocked
00048011581309	7000124223	3M™ Performance Plus Duct Tape 8979N (Nuclear), Red, 24 mm x 54.8 m, 12.1 mil, 48 per case	Stocked
00048011539140	7000049014	3M™ Performance Plus Duct Tape 8979N (Nuclear), Red, 48 mm x 54.8 m, 12.1 mil, 24 per case	Stocked
00048011539157	7010334653	3M™ Performance Plus Duct Tape 8979N (Nuclear), Red, 72 mm x 54.8 m, 12.1 mil, 12 per case	Stocked
00051115259258	7010374791	3M™ Performance Plus Duct Tape 8979N (Nuclear), Red, 96 mm x 54.8 m, 12.1 mil, 12 per case	Make to Order
00051115259258	7000124268	3M™ Performance Plus Duct Tape 8979N (Nuclear), Slate Blue, 48 mm x 54.8 m, 12.1 mil, 24 per case	Stocked